The compact approach to playback flexibility!



Step up to quality multichannel operation in your present monaural space limitations. The Lang Tape Play Unit features a tape recorder head pre-amp line amplifier. The high and low frequency turnover points are adjustable from the front panel via locking shaft adjustments. The gain of the unit is also adjustable from the front panel.

Amplifier circuitry is mounted on a plug-in printed circuit card. A built-in output transformer provides balanced output connections. Radio frequency and switching interference is eliminated by a shield connector compartment and feed-thru

Note: 90 usec, 120 usec, and 200 usec curves also available.

SPECIFICATIONS:

FREQUENCY RESPONSE

±1 db Standard 50 usec NAB

Playback Curve

NOISE

- 67 dbm for Full Track

DISTORTION

- 62 dbm for Half Track

Less than 1% at levels up to +20

dbm into 600 ohms.

(Typical Production Unit delivers + 24 dbm)

CLIPPING LEVEL

In excess of +24 dbm

POWER REQUIREMENT +35 Volts @ 50-80 ma.

- 28 Volts @ 50 ma.

For all your audio needs - LOOK TO LANG!

DIMENSIONS

134" W x 5" H x 12" D

CONNECTORS

Standard Cannon and Clinch Jones

on rear panel

PANEL FINISH

Stainless Steel, Black Lettering

ACCESSORIES:

LPS-1

Power Supply for 4 LTP-1 Units

Power Supply for 10 LTP-1 Units

RACK MOUNT FRAME

Up to 8 LTP-1 Units in 51/4" x

19" Rack Space

ELECTRONICS, INC.

507 FIFTH AVENUE NEW YORK, N.Y. 10017